




The Tool-Free DE.

There's never been a DE filter as easy to install, inspect and service as EarthWorks. No bolts. No clamps. No tools. **Everything else is history.**

Get more details on EarthWorks with our **FREE VIDEO** offer by calling 800-635-7500, 24-hours-a-day.




■ Ring-Lok™ Access for easy servicing.



■ Seal-Ring Key fits into tank assembly to break o-ring seal easily.



■ Modular Grid Assembly allows easy one-piece removal for cleaning.



■ **EARTHSHAKE** Regeneration extends filter cycles.



■ 5-Year Warranty on the structure of the tank against failure from the date of installation.

The **EARTHWORKS™** DE Filter by

JACUZZI



1. 2" FPT Ground Level Plumbing allows for easy installation.
2. Function Selector Handle allows you to choose between filter and backwash with a simple move of the handle.
3. Exclusive EARTHSHAKE Regeneration allows you to extend filter cycles by moving the selector handle from "Filter" to "Backwash" to "Filter" while pump is in operation.
4. Exclusive Ring-Lok™ allows easy access to grid assembly with a simple twist.
5. Modular Grid Assembly allows easy one-piece removal for inspection and cleaning.
6. Vertical Straight Grids reduce bridging and provide more uniform flow during filtration and backwash.
7. Top-mounted Manifold provides automatic air bleed and insures 100% grid utilization.
8. Built-in Function Selector (Valve) is easily removed for servicing. It eliminates an external valve and excess plumbing.
9. Foam Molded, Engineered Thermoplastic Tank provides the latest in high-tech, non-corrosive construction for durability and strength.

The EARTHWORKS™ DE Filter by Jacuzzi.



- Ring-Lok™ Separation Tank. Exclusive Ring-Lok™ for easy no-tool access. Thermoplastic tank is corrosive resistant. Tapered bag allows full flow during backwash and optimizes DE collection capacity.



■ EarthWorks DE Filter Dimensions

Model	A	B
EW75	41"	24"
EW100	47"	24"
EW125	53"	24"
EW150	59"	24"

■ EarthWorks DE Filter Performance

Model	Flow Rate (GPM)	Area Sq. Ft.	Total Gallons Circulated 8 Hrs.	DE Required
EW75	84	40	30200	6 lbs
EW100	108	54	38800	8 lbs
EW125	140	70	50400	10 lbs
EW150	168	84	60400	12 lbs

*2.5-3 GPM sq.ft. filtration rate.

MEMBER



Full Service
Factor Units

AUTHORIZED SOLE DISTRIBUTOR



JACUZZI
SOLUTIONS THROUGH INNOVATION™